





2022 ThermoProbe, Inc. Pricing Guide

Standard Thermometers (Most popular and usually in stock.)

Effective
Jan. 01, 2022

Item	Description	
TP7D-075-SW-SM	TP7-D Thermometer, 75ft (23m) cable, Standard Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEx Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,303.32
TP7D-25M-EW-MM	TP7-D Thermometer, 25 meter (82 feet) cable, Extra Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEx Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,320.02
TP7D-25M-SW-MM	TP7-D Thermometer, 25 meter (82 feet) cable, Standard Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEx Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,320.02
TP9A-075-SW-SM	TP9-A Thermometer, 75 feet (23m) cable, Standard Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEx Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,225.34
TP9A-075-AW-NM	TP9-A Thermometer, 75 feet (23m) cable, Asphalt Weight Probe, No Brass Markers, ATEX/IECEx Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,258.76
TP9A-075-EW-SM	TP9-A Thermometer, 75 feet (23m) cable, Extra Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEx Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,258.76
TP9A-25M-EW-MM	TP9-A Thermometer, 25 meter (82 feet) cable, Extra Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEx Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,258.76
TL3A-08	TL3-A Thermometer, 8 in. (20cm) sensor length, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, includes hard case	\$624.57
TL3A-12	TL3-A Thermometer, 12 in. (30cm) sensor length, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, includes hard case.	\$624.57
TL3R-08	TL3-R Thermometer, 8 inch Sensor including hard case, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, Calibration Report in Fahrenheit/Celsius	\$1,009.45
TL3R-12	TL3-R Thermometer, 12 inch Sensor including hard case, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, Calibration Report in Fahrenheit/Celsius	\$1,009.45

Laboratory/Reference Thermometers



Item	Description	2022 Price (USD)
TL3A-04	TL3-A Thermometer, 4 in. (10cm) sensor length, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, includes hard case	\$840.33
TL3A-06	TL3-A Thermometer, 6 in. (15cm) sensor length, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, includes hard case	\$840.33
TL3A-08	TL3-A Thermometer, 8 in. (20cm) sensor length, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, includes hard case	\$624.57
TL3A-12	TL3-A Thermometer, 12 in. (30cm) sensor length, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, includes hard case.	\$624.57
TL3A-14	TL3-A Thermometer, 14 in. (35cm) sensor length, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C	\$840.33
TL3A-16	TL3-A Thermometer, 16 in. (40cm) sensor length, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C	\$840.33
TL3A-18	TL3-A Thermometer, 18 in. (46cm) sensor length, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C	\$840.33
TL3A-24	TL3-A Thermometer, 24 in. (60cm) sensor length, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C	\$840.33
TL3R-08	TL3-R Thermometer, 8 inch Sensor including hard case, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, Calibration Report in Fahrenheit/Celsius	\$1,009.45
TL3R-12	TL3-R Thermometer, 12 inch Sensor including hard case, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, Calibration Report in Fahrenheit/Celsius	\$1,009.45
TL3R-16	TL3-R Thermometer, 16 inch Sensor, ATEX/IECEx Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, Calibration Report in Fahrenheit/Celsius	\$1,120.31



2022 ThermoProbe, Inc. Pricing Guide

TL3W-04	TL3-W Thermometer, 4 in. (10cm) sensor length, ATEX/IECEX Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, includes hard case	\$965.24
TL3W-06	TL3-W Thermometer, 6 in. (15cm) sensor length, ATEX/IECEX Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, includes hard case	\$965.24
TL3W-08	TL3-W Thermometer, 8 in. (20cm) sensor length, ATEX/IECEX Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, includes hard case	\$738.12
TL3W-12	TL3-W Thermometer, 12 in. (30cm) sensor length, ATEX/IECEX Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C, includes hard case.	\$738.12
TL3W-16	TL3-W Thermometer, 16 in. (40cm) sensor length, ATEX/IECEX Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C	\$965.24
TL3W-18	TL3-W Thermometer, 18 in. (46 cm) sensor length, ATEX/IECEX Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C	\$965.24
TL3W-24	TL3-W Thermometer, 24 in. (60cm) sensor length, ATEX/IECEX Certification (Ex ia IIC T4 Ga), Ambient temperature range -20°C to +40°C	\$965.24
TL2-A	TL2-A 2-channel precision bench top thermometer without sensor , Configurable RTD and SPRT combinations, Available 2 channel temperature measurement, 0.001 degree resolution, Implements ITS-90 or Callendar-Van Dusen calibration coefficients, Displays temperature in Celsius, Fahrenheit, Kelvin or Ohms. Backlit, large LCD character display, USB Type 'A' PC interface, USB Type 'B' flash memory interface, user programmable relay output interface.	\$2,100.00
TL2-A-1SEN	TL2-A 2-channel precision bench top thermometer with 1 sensor , Configurable RTD and SPRT combinations, Available 2 channel temperature measurement, 0.001 degree resolution, Implements ITS-90 or Callendar-Van Dusen calibration coefficients, Displays temperature in Celsius, Fahrenheit, Kelvin or Ohms. Backlit, large LCD character display, USB Type 'A' PC interface, USB Type 'B' flash memory interface, user programmable relay output interface.	\$2,625.00
TL2-A-2SEN	TL2-A 2-channel precision bench top thermometer with 2 sensors , Configurable RTD and SPRT combinations, Available 2 channel temperature measurement, 0.001 degree resolution, Implements ITS-90 or Callendar-Van Dusen calibration coefficients, Displays temperature in Celsius, Fahrenheit, Kelvin or Ohms. Backlit, large LCD character display, USB Type 'A' PC interface, USB Type 'B' flash memory interface, user programmable relay output interface.	\$3,150.00
TL3-08	TL3 Thermometer, 8 in. (20cm) sensor length, Ambient temperature range -20°C to +40°C, includes hard case.	\$373.75
TL3-12	TL3 Thermometer, 12 in. (30cm) sensor length, Ambient temperature range -20°C to +40°C, includes holster.	\$373.75

Gauging Thermometers

Model TP7-D



Item	Description	2022 Price (USD)
TP7D-012-EW-NM	TP7-D Thermometer, 12ft (4m) cable, Extra Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-012-RC-NM	TP7-D Thermometer, 12ft (4m) cable, Railcar Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-012-SW-NM	TP7-D Thermometer, 12ft (4m) cable, Standard Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-025-AW-SM	TP7-D Thermometer, 25ft (7.5m) cable, Asphalt Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-025-EW-NM	TP7-D Thermometer, 25ft (7.5m) cable, Extra Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-025-EW-SM	TP7-D Thermometer, 25ft (7.5m) cable, Extra Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-025-RC-NM	TP7-D Thermometer, 25ft (7.5m) cable, Railcar Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52



2022 ThermoProbe, Inc. Pricing Guide

TP7D-025-SW-NM	TP7-D Thermometer, 25ft (7.5m) cable, Standard Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-025-SW-SM	TP7-D Thermometer, 25ft (7.5m) cable, Standard Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-050-AW-NM	TP7-D Thermometer, 50ft (15m) cable, Asphalt Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-050-AW-SM	TP7-D Thermometer, 50ft (15m) cable, Asphalt Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-050-EW-NM	TP7-D Thermometer, 50ft (15m) cable, Extra Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-050-EW-SM	TP7-D Thermometer, 50ft (15m) cable, Extra Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-050-SW-NM	TP7-D Thermometer, 50ft (15m) cable, Standard Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-050-SW-SM	TP7-D Thermometer, 50ft (15m) cable, Standard Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,448.13
TP7D-075-AW-NM	TP7-D Thermometer, 75ft (23m) cable, Asphalt Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-075-AW-SM	TP7-D Thermometer, 75ft (23m) cable, Asphalt Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-075-EW-NM	TP7-D Thermometer, 75ft (23m) cable, Extra Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-075-EW-SM	TP7-D Thermometer, 75ft (23m) cable, Extra Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-075-SW-NM	TP7-D Thermometer, 75ft (23m) cable, Standard Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-075-SW-SM	TP7-D Thermometer, 75ft (23m) cable, Standard Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,303.32
TP7D-10M-EW-MM	TP7-D Thermometer, 10 meter (33 feet) cable, Extra Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-10M-SW-MM	TP7-D Thermometer, 10 meter (33 feet) cable, Standard Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-110-AW-NM	TP7-D Thermometer, 110ft (34m) cable, Asphalt Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-110-AW-SM	TP7-D Thermometer, 110ft (34m) cable, Asphalt Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-110-EW-NM	TP7-D Thermometer, 110ft (34m) cable, Extra Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-110-EW-SM	TP7-D Thermometer, 110ft (34m) cable, Extra Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-110-SW-NM	TP7-D Thermometer, 110ft (34m) cable, Standard Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-110-SW-SM	TP7-D Thermometer, 110ft (34m) cable, Standard Weight Probe, Brass Markers at 5ft (1.5m) intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,448.13
TP7D-25M-AW-MM	TP7-D Thermometer, 25 meter (82 feet) cable, Asphalt Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-25M-EW-MM	TP7-D Thermometer, 25 meter (82 feet) cable, Extra Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,320.02
TP7D-25M-SW-MM	TP7-D Thermometer, 25 meter (82 feet) cable, Standard Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,320.02
TP7D-30M-AW-MM	TP7-D Thermometer, 30 meter (98 feet) cable, Asphalt Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,559.52
TP7D-30M-EW-MM	TP7-D Thermometer, 30 meter (98 feet) cable, Extra Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,448.13
TP7D-30M-SW-MM	TP7-D Thermometer, 30 meter (98 feet) cable, Standard Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,448.13
TP7D-35M-EW-MM	TP7-D Thermometer, 35 meter (115 feet) cable, Extra Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,448.13



2022 ThermoProbe, Inc. Pricing Guide

TP7D-35M-SW-MM	TP7-D Thermometer, 35 meter (115 ft) cable, Standard Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,448.13
TP7D-3	TP7-D Thermometer with a 3-conductor probe assembly to achieve higher accuracy using 3 conductors to improve resistence stability.	\$1,785.00

Model TP9-A



Item	Description	2022 Price (USD)
TP9A-012-EW-NM	TP9-A Thermometer, 12ft (4m) cable, Extra Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-012-RC-NM	TP9-A Thermometer, 12ft (4m) cable, Railcar Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-012-SW-NM	TP9-A Thermometer, 12ft (4m) cable, Standard Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-025-AW-SM	TP9-A Thermometer, 25ft (7.5m) cable, Asphalt Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-025-EW-NM	TP9-A Thermometer, 25ft (7.5m) cable, Extra Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-025-EW-SM	TP9-A Thermometer, 25ft (7.5m) cable, Extra Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-025-RC-NM	TP9-A Thermometer, 25ft (7.5m) cable, Railcar Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-025-SW-NM	TP9-A Thermometer, 25ft (7.5m) cable, Standard Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-025-SW-SM	TP9-A Thermometer, 25ft (7.5m) cable, Standard Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-050-AW-NM	TP9-A Thermometer, 50ft (15m) cable, Asphalt Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-050-AW-SM	TP9-A Thermometer, 50ft (15m) cable, Asphalt Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-050-EW-NM	TP9-A Thermometer, 50ft (15m) cable, Extra Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-050-EW-SM	TP9-A Thermometer, 50ft (15m) cable, Extra Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-050-SW-NM	TP9-A Thermometer, 50ft (15m) cable, Standard Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-050-SW-SM	TP9-A Thermometer, 50ft (15m) cable, Standard Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-075-AW-NM	TP9-A Thermometer, 75 feet (23m) cable, Asphalt Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,258.76
TP9A-075-AW-SM	TP9-A Thermometer, 75 feet (23m) cable, Asphalt Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-075-EW-NM	TP9-A Thermometer, 75 feet (23m) cable, Extra Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-075-EW-SM	TP9-A Thermometer, 75 feet (23m) cable, Extra Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,258.76
TP9A-075-SW-NM	TP9-A Thermometer, 75 feet (23m) cable, Standard Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-075-SW-SM	TP9-A Thermometer, 75 feet (23m) cable, Standard Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,225.34
TP9A-10M-EW-MM	TP9-A Thermometer, 10 meter (33 feet) cable, Extra Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83



2022 ThermoProbe, Inc. Pricing Guide

TP9A-10M-SW-MM	TP9-A Thermometer, 10 meter (33 feet) cable, Standard Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-110-AW-NM	TP9-A Thermometer, 110 feet (34m) cable, Asphalt Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-110-AW-SM	TP9-A Thermometer, 110 feet (34m) cable, Asphalt Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-110-EW-NM	TP9-A Thermometer, 110 feet (34m) cable, Extra Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-110-EW-SM	TP9-A Thermometer, 110 feet (34m) cable, Extra Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-110-SW-NM	TP9-A Thermometer, 110 feet (34m) cable, Standard Weight Probe, No Brass Markers, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-110-SW-SM	TP9-A Thermometer, 110 feet (34m) cable, Standard Weight Probe, Brass Markers at 5 feet intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,392.43
TP9A-25M-AW-MM	TP9-A Thermometer, 25 meter (82 feet) cable, Asphalt Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,392.43
TP9A-25M-EW-MM	TP9-A Thermometer, 25 meter (82 feet) cable, Extra Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,258.76
TP9A-25M-SW-MM	TP9-A Thermometer, 25 meter (82 feet) cable, Standard Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-30M-AW-MM	TP9-A Thermometer, 30 meter (98 feet) cable, Asphalt Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-30M-EW-MM	TP9-A Thermometer, 30 meter (98 feet) cable, Extra Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-30M-SW-MM	TP9-A Thermometer, 30 meter (98 feet) cable, Standard Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-35M-EW-MM	TP9-A Thermometer, 35 meter (115 feet) cable, Extra Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-35M-SW-MM	TP9-A Thermometer, 35 meter (115 ft) cable, Standard Weight Probe, Brass Markers at 1 meter intervals, ATEX/IECEX Certification (Ex ia IIB T4 Ga), Ambient temperature range -20°C to +40°C	\$1,503.83
TP9A-3	TP9-A Thermometer with a 3 conductor probe assembly to achieve higher accuracy using 3 conductors to improve resistance stability.	\$1,785.00